

Consent For Operation (CFO-Air.Water)

Consent No. AW-321392 Valid upto: 30/06/2026

Industry Colour: RED Industry Scale: MEDIUM **Karnataka State Pollution Control Board** Parisara Bhavana, No. 49, Church Street, Bengaluru-560001 Tele: 080-25589112/3, 25581383

Fax:080-25586321 email id: ho@kspcb.gov.in

5 pages including annexure & excluding additional (This document contains

conditions)

Combined Consent Order No. AW-321392

PCB ID:

10269

Date: 09/11/2020

Combined consent for discharge of effluents under the Water (Prevention and Control of Pollution) Act , 1974 and emission under the Air (Prevention and Control of Pollution)Act , 1981

1. Application filed by the applicant/organization on 19/10/2020 Ref:

on 16/10/2020

Industry/organization/by RO,

3. Proceedings of the CCM dated 27/10/2020

.held on 20/10/2020

Consent is hereby granted to the Occupier under Section 25(4) of the Water (Prevention & Control of Pollution) Act, 1974 (herein referred to as the Water Act) & Section 21 of Air (Prevention & Control of Pollution) Act, 1981, (herein referred to as the Air Act) and the Rules and Orders made there under and authorized the Occupier to operate /carryout industry/activity & to make discharge of the effluents & emissions confirming to the stipulated standards from the premises mentioned below and subject to the terms and conditions as detailed in the Schedule Annexed to this order.

Location:

Name of the Industry: Ramky Enviro Engineers Ltd., (Tsdf)

75 to 85 of Pemmenahalli & 7 & 9 of Thimmanayakanahalli, Towards Doddaballapur Road, NH-207, Address:

KIADB Industrial Area,

Industrial Area: Dobaspet III Phase I.A Somapura, Nelamangala Taluk,

Taluk:

Nelmangala, District: Bangalore Rural

CONDITIONS:

a) Discharge of effluents under the Water Act:

Sr	Water Code	WC(KLD)	WWG(KLD)	Remark
1	Domestic Purpose	7.000	5.600	Shall be disposed to Septic
				tank & Soak Pit(Refer
				annexure C)
2	Others	2.000	1.900	Water is used for scrubber
				make up and scrubber liquid
				shall be treated in the spray
				dryer. (Refer annexure C)
3	Others	0.500	0.500	laboratory washing shall be
				Collected in leachate
				collection tank and shall be
				treated in the spray drier
				(Refer annexure C)
4	Others	99.000	0.000	Water is used for spray drier
				if there is no leachate
				available(Refer annexure C)

b) Discharge of Air emissions under the Air Act from the following stacks etc.

Limits specified refer schedule Sl. No. Description of chimney/outlet

The details of Sources, control equipments and its specification, type of fuel, constituents to be controlled in emissions etc. are detailed in Annexure-II.

The consent for operation is granted considering the following activities/Products;

Sr	Product Name	Applied Qty/Month	Unit
1	Incinaration of Hazardous waste	1044.0000	M.T
2.	treatment storage and disposal of landfillable, hazardous waste	3333 3300	МТ

This consent is valid for the period from

01/07/2021

to

30/06/2026

Ramky Enviro Engineers Ltd., (Tsdf)

Dobbaspet

COPY TO:

The Environmental Officer, KSPCB, Regional Office Nelamangala for information and necessary action.

- Master Register.
- 3. Case file.

Page-1 e_outwardno35276--09/11/2020 Printed from XGN



Consent For Operation (CFO-Air, Water)

Consent No. AW-321392 Valid upto: 30/06/2026

Industry Colour: RED Industry Scale: MEDIUM

Karnataka State Pollution Control Board Parisara Bhavana,No.49, Church Street,Bengaluru-560001 Tele: 080-25589112/3, 25581383 Fax:080-25586321

email id: ho@kspcb.gov.in

(This document contains

5 pages including annexure & excluding additional conditions)

Consent Fee paid : Rs. 900000

SCHEDULE

TERMS AND CONDITIONS

A. TREATMENT AND DISPOSAL OF EFFLUENTS UNDER THE WATER ACT.

- 1. The discharge from the premises of the occupier shall pass through the terminal manhole/manholes where from the Board shall be free to collect samples in accordance with the provisions of the Act/Rules made there under.
- 2(a). The sewage/domestic effluent shall be treated in septic tank and with soak pit. No overflow from the soak pit is allowed. The septic tank and soak pit shall be as per IS 2470 Part-I & Part-II.
- 2(b). The treated sewage effluent discharged shall conform to the standards specified in Annexure-I.
- 3(a). The trade effluent generated in the industry shall be treated in the ETP and treated effluent shall confirm to the standards stipulated by the Board in Annexure-I
- 3(b). The trade effluent shall be handed over to CETP and maintain logbook of effluent generated & sent every day.
- 4. The applicant shall install flow measuring/recording devices to record the discharge quantity and maintain the record.
- 5. The applicant shall not change or alter either the quality or the quantity or the place of discharge or temperature or the point of discharge without the previous consent/permission of the Board.
- 6. The applicant shall not allow the discharge from the other premises to mix with the discharge from his premises. Storm water shall not be allowed to mix with the effluents on the upstream of the terminal manhole where the flow measuring devices are installed.
- 7. The daily quantity of domestic effluent and trade effluent from the industry shall not exceed the limits as indicated in this consent order:
- 8. The applicant shall discharge the effluents only to the place mentioned in the Consent order and discharge of treated/untreated outside the premises is not permitted.

B. EMISSIONS:

- 1. The discharge of emissions from the premises of the applicant shall pass through the air pollution control equipment and discharged through stacks/chimneys mentioned in **Annexure-II** where from the Board shall be free to collect the samples at any time in accordance with the provisions of the Act and Rules made there under. The tolerance limits of the constituents forming the emissions in each of the stacks shall not exceed the limits laid down in Annexure-II.
- 2. The applicant shall provide port holes for sampling of emission, access platforms for carrying out stack sampling, electrical points and all other necessary arrangements including ladder as indicated in Annexure-II.
- 3. The applicant shall upgrade/modify/replace the control equipment with prior permission of the Board.

C.MONITORING & REPORTING:

- 1. The applicant shall get the samples of effluents & emissions collected and get them analyzed once a month/either by in house monitoring laboratory or through EP approved laboratories for the parameters as Indicated in Annexure I & II.
- 2. The applicant shall maintain log books to reflect the working condition of pollution control systems and also self monitoring results and keep it open for inspection.

D. SOLID WASTE (OTHER THAN HAZARDOUS WASTE) DISPOSAL:

- 1.The applicant shall segregate solid waste from Hazardous Waste, Municipal Solid Waste and store it properly till treatment/disposal without causing pollution to the surrounding Environment.
- 2.The solid waste generated shall be handled & disposed by scientific method without causing eye sore to the general public and to the surrounding environment.



Consent No. AW-321392 Valid upto: 30/06/2026

Industry Colour: RED Industry Scale: MEDIUM **Karnataka State Pollution Control Board** Parisara Bhavana, No. 49, Church Street, Bengaluru-560001 Tele: 080-25589112/3, 25581383 Fax:080-25586321

email id: ho@kspcb.gov.in

(This document contains 5 pages including annexure & excluding additional conditions)

E. NOISE POLLUTION CONTROL:

The applicant shall ensure that the ambient noise levels within its premises shall not exceed the limits i.e 75 dB(A) Leq during day time and 70 dB(A) Leq during night time as specified in under the Air (Prevention and Control of Pollution) Act, 1981.

F. HAZARDOUS AND OTHER WASTES (MANAGEMENT & TRANSBOUDARY MOVEMENT)Rules2016:

The applicant shall comply with the provisions of the Hazardous and other Wastes (Management & Transboundry Movement) Rules 2016.

G. GENERAL CONDITIONS:

- The applicant shall not allow the discharge from the other premises to mix with the discharge from his premises.
- The applicant shall promptly comply with all orders and instructions issued by the Board from time to time or any other officers of the Board duly authorized in this behalf.
- The applicant shall set-up Environmental Cell comprising of qualified and competent personnel for complying with the conditions specified.
- 4. The Board reserves the right to review, impose additional conditions, revoke, change or alter terms and conditions of this consent.
- 5. The applicant shall forthwith keep the Board informed of any accidental discharge of emissions/effluents into the atmosphere in excess of the standards laid down by the Board. The applicant shall also take corrective steps to mitigate the impact.
- The applicant shall provide alternate power supply sufficient to operate all Pollution control equipments.
- The entire premises shall always be kept clean. The effluent holding area, inspection chambers, outlets, flow measuring points should made easily approachable.
- 8. The applicant shall display the consent granted in a prominent place for perusal of the inspecting officers of the Board.
- 9. The applicant his heirs, legal representatives or assignee shall have no claims what so ever to the continuation or renewal of this consent after expiry of the validity of consent.
- 10. The applicant shall make an application for consent for subsequent period at least 45 days before expiry of this consent.
- 11. The applicant shall develop and maintain adequate green belt all around the periphery.
- 12. The applicant shall provide rain water harvesting system and shall provide proper storm water management system.
- 13. This consent is issued without prejudice to any Court Cases pending in any Hon'ble Court
- 14. The applicant shall furnish the Environmental statement for every financial year ending with 31st March in Form-V as per Environment (Protection) Rules, 1986. The statement shall be furnished before the end of September.
- 15. The applicant shall display flow diagram of the pollution control system near the pollution contol system/s.



<u>Consent For Operation</u> (<u>CFO-Air,Water</u>)

Consent No. AW-321392 Valid upto: 30/06/2026

Industry Colour: RED Industry Scale: MEDIUM

Karnataka State Pollution Control Board Parisara Bhavana,No.49, Church Street,Bengaluru-560001 Tele: 080-25589112/3, 25581383 Fax:080-25586321

email id: ho@kspcb.gov.in

(This document contains 5 pages including annexure & excluding additional conditions)

NOTE:

The Conditions Nil mentioned in the schedule are not applicable.

Additional Conditions:

1. The applicant shall follow the conditions as stipulated in Annexure-A,B, C & D

Chi m.N o.	Chimne y attached to	KVA	Minimum chimney height to be provided above ground level (in Mts)	Constituents to be controlled in the emission	Tolerance limits mg/NM3	Fuel	Air pollution Control equipment to be installed,in addition to chimney height as per col.(4)	pollution control
1	Any Other	Laborato ry	3	PM(mg/NM3),SO2 (PPM),NOx(PPM)	Acid mist- 10mg/m3,		SCR	Before commissioning.
2	Incinera tor	1.5ton/hr	40	PM(mg/NM3),SO2 (PPM),NOx(PPM)	50,200,400	DIE	4CS,FIL,DU S,MUL,PRT, SCR,SET	Before commissioning.
3	Any Other	Stablisati on section	3	PM(mg/NM3),SO2 (PPM),NOx(PPM)	Acid Mist - 10mg/m3	1/2-	HDC	Before commissioning.
4	D.G. Sets	500 KVA	5	PM(mg/NM3),SO2 (PPM),NOx(PPM)	150,100,50	DIE	AEC,PRT	Before commissioning.
5	D.G. Sets	62.5 KVA	3	PM(mg/NM3),SO2 (PPM),NOx(PPM)	150,100,50	DIE	PRT	Before commissioning.

Note:

SCR : Scrubber

4CS,FIL, : 4 Stage Cyclone Seperator

DUS,MU L,PRT,SC R,SET

HDC : Hood Cover

AEC,PRT: Accoustic Enclosures

PRT: Port Hole

Note:

1. The Noise levels within the premises shall not exceed 75 dB (A) leq during day time and 70 dB(A) leq during night

2. The DG set shall be provided with acoustic measures as per SI.No.94 in Schedule-I of Environment (Protection)Rules.

3. There shall be no smell or odour nuisance from the industry.



Consent For Operation (CFO-Air, Water)

Consent No. AW-321392 Valid upto: 30/06/2026

Industry Colour: RED Industry Scale: MEDIUM

Karnataka State Pollution Control Board Parisara Bhavana,No.49, Church Street,Bengaluru-560001 Tele: 080-25589112/3, 25581383 Fax:080-25586321

email id: ho@kspcb.gov.in

(This document contains 5 pages including annexure & excluding additional conditions)

LOCATION OF SAMPLING PORTHOLES, PLATFORMS, ELECTRICAL OUTLET.

1. Location of Portholes and approach platform:

Portholes shall be provided for all chimneys, stacks and other sources of emission. These shall serve as the sampling points. The sampling point should be located at a distance equal to atleast eight times the stack or duct diameters downstream and two diameters upstream from source of low disturbance such as a Bend, Expansion, Construction Valve, Fitting or Visible Flame for rectangular stacks, the equivalent diameter can be calculated from the following equation.

- 2. The diameter of the sampling port should not be less than 100 mm dia". Arrangements should be made so that the porthole is closed firmly during the non sampling period
- 3. An easily accessible platform to accommodate 3 to 4 persons to conveniently monitor the stack emission from the portholes shall be provided. Arrangements for an Electric Outlet Point of 230 V 15 A with suitable switch control and 3 Pin Point shall be provided at the Porthole location.
- 4. The ladder shall be provided with adequate safety features so as to approach the monitoring location with ease.

For and on behalf of the Karnataka State Pollution Control Board